

Appl. No. 10/643,557  
Amdt Dated: Oct. 7, 2005  
Reply to Office Action of Aug. 8, 2005

### **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### **Listing of Claims:**

1-15. (canceled)

16. (currently amended) A mounting apparatus assembly comprising:

a storage device defining two opposite side faces with a plurality of fixing holes in at least one of said side faces; and

a mounting bracket comprising:

a bottom wall;

opposite first and second side walls extending from two opposite side edges of the bottom wall, said storage device being seated upon the bottom wall with the two side faces respectively engaged with the corresponding side walls of the bracket; and

a plurality of locating pins extending inwardly from the first side wall and received in the corresponding fixing holes, respectively; wherein

said mounting bracket further includes a plurality of fixing structures located oppositely far away from the first side wall and fixing said storage device relative to the bracket, wherein

at least one of said first and second side walls is outwardly deflectable relative to the bottom wall for downward loading the storage device into the bracket;.

Appl. No. 10/643,557  
Amdt Dated: Oct. 7, 2005  
Reply to Office Action of Aug. 8, 2005

wherein the second side wall comprises a first vertical wall, a second vertical wall and a horizontal connecting wall connecting the first and second vertical walls.

17. (canceled)

18. (currently amended) The mounting apparatus assembly as described in claim 16, wherein the fixing structures comprises at least one through hole defined in the second side wall.

19. (original) The mounting apparatus assembly as described in claim 16, wherein the second side wall perpendicularly extends from the bottom wall of the mounting bracket, parallel to the first side wall.

20. (currently amended) The mounting apparatus assembly as described in claim 19, wherein each of the fixing structures comprises a fixing tab extending from the bottom wall, parallel to and spaced from the second side wall, and the fixing tab has a through hole corresponding to the fixing hole defined in the opposite side face of the storage device.

21. (currently amended) The mounting apparatus assembly as described in claim 16, wherein the fixing structure comprises at least one protrusion protruding ~~from~~ from second side wall of the mounting bracket.

22. (original) The mounting apparatus assembly as described in claim 21, wherein the protrusion abuts against a top of the storage device to prevent the storage device from upwardly deflecting.